












## Technical Bulletin – Waterproof Aluminium Decking

<b>Product</b>	<b>NexGEN Premium Aluminium Decking</b>
<b>Report</b>	<b>DryDeck 2.0</b>
<b>Description</b>	NexGEN DryDeck 2.0 is an aluminium decking board with an innovative waterproof tongue and groove design that creates beautiful, low maintenance, fireproof deck surface. DryDeck 2.0 watertight decking boards provide the added bonus of an integrated gutter system for a dry, usable area under the deck. The safe, non- skid textured surface naturally stays cooler to the touch than traditional decking. DryDeck 2.0 was designed and engineered for high traffic use in the most demanding applications.
<b>Key Information</b>	Slip-resistant P5 rated surface. 4 weeks lead time. Delivery cost to site to be quoted per project. The gutter groove between boards can be revealed or concealed to suit aesthetic. Noise suppression tape available. Apply continuously along the central support leg. Requires a 1 in 100 fall (1cm per meter). Support frame required at 450mm centres. The long edge of the decking board to run parallel to fall. Waterproof but not watertight. Not suitable over habitable rooms. Joiners suitable to extend boards end to end where in excess of 6m length is required. NB: the use of joiners will allow water ingress. Self-mating slat is a 2-piece rectangular section suitable as a riser to conceal the subfloor. A 6m Self-mating slat can be cut into smaller sections as required. Finishing Base/Top: Components for the outer perimeters to conceal the cut edge.
<b>Features</b>	Non-combustible: DryDeck 2.0 will simply not ignite or burn. BAL Flame Zone Rated. Durable: DryDeck 2.0 is impervious to insects and will not split, splinter, decay, or rot. Cool to the touch: aluminium’s high thermal conductivity rapidly dissipates heat, creating a cooler surface than most traditional types of decking. Family friendly: no harmful chemicals yet easy to clean and stain resistant Waterproof: DryDeck 2.0 unique design creates a dry space beneath a deck, suitable for storage or alfresco if used on a balcony or similar.
<b>Material</b>	6050 Marine Grade Aluminium Coatings: Interpon D1000, D2015, DSTF
<b>Warranty</b>	15 Year Woodgrain Colour Warranty 20 Year Ultriva™ Warranty



## Technical Bulletin – Waterproof Aluminium Decking

 <p>150mm Decking Board 6050mm</p>	 <p>Decking Starter Strip 5650mm</p>	 <p>Concealed Finishing Angle 5050mm &amp; 6050mm</p>
 <p>Concealed Finishing Angle "Infill" 6050mm</p>	 <p>Finishing Angle 5050 &amp; 6050mm</p>	 <p>Finishing Base 5650mm</p>
 <p>Finishing Top Small 5650mm</p>	 <p>Finishing Top Large 5650mm</p>	 <p>Decking Joiner Base 5650mm</p>
 <p>Decking Joiner Top 5650mm</p>	 <p>Self mating slat 150 x 16</p>	

